Valvoline.	Page: 1
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Synpower™

SYNTHETIC GREASE

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet

Valvoline LLC
3499 Blazer Parkway
Lexington, KY 40509
United States of America

SDS@valvoline.com

Emergency telephone number
1-800-VALVOLINE

Regulatory Information Number
1-800-TEAMVAL

Product Information
1-800-TEAMVAL

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

GHS Label element

Hazard pictograms :



Signal Word : Warning

Hazard Statements : Causes serious eye irritation.

Precautionary Statements : **Prevention:**

Wash skin thoroughly after handling. Wear eye protection/ face protection.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

If eye irritation persists: Get medical advice/ attention.

Other hazards

Valvoline.	Page: 2
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
OLEFIN POLYMER	9002-88-4	Not a hazardous substance or mixture.	9.99
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 2; H401 Aquatic Chronic 2; H411	2.50
MOLYBDENUM DISULFIDE	1317-33-5	Not a hazardous substance or mixture.	2.50

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.

If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on skin, rinse well with water.

First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Valvoline.	Page: 3
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways) Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Oxides of phosphorus

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Use personal protective equipment.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

Valvoline	Page:
SAFETY DATA SHEET	Revision Date: 07/31/2010
	Print Date: 11/1/2010
	SDS Number: R025703
Synpower™ SYNTHETIC GREASE	Version: 1.
VV985	

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.

Do not smoke.

Container hazardous when empty. Avoid contact with skin and eyes.

Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
MOLYBDENUM DISULFIDE	1317-33-5	TWA	3 mg/m3 Respirable fraction. (as Mo)	ACGIH
		TWA	10 mg/m3 Inhalable fraction. (as Mo)	ACGIH
		PEL	15 mg/m3 Total dust. (as Mo)	OSHA_TRA NS
		TWA	10 mg/m3 Total dust. (as Mo)	Z1A

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

Engineering measures : Provide sufficient mechanical (general and/or local exhaust)

ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

apparent adverse effects.

Personal protective equipment

Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate

cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by airpurifying respirators is limited. Use a positive pressure, airsupplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not

provide adequate protection.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Safety glasses

Skin and body protection : Wear as appropriate:

impervious clothing

Safety shoes

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures Wash hands before breaks and at the end of workday.

> When using do not eat or drink. When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Physical state liquid

Colour dark grey

Odour No data available

Odour Threshold : No data available

: No data available рΗ

Valvoline.	Page: 6
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

Melting point/freezing point : 500 °F / 260 °C

Boiling point/boiling range : 700 °F / 371 °C

Flash point : $419 \,^{\circ}\text{F} / 215 \,^{\circ}\text{C}$

Evaporation rate :

No data available

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure :

No data available

Relative vapour density : No data available

Relative density :

No data available

Density : 0.919 g/cm3 (20 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : > 315 °C

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

carbon dioxide and carbon monoxide products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure

Skin contact Eye Contact

Ingestion

Acute toxicity

Not classified based on available information.

Product:

: LD 50 (Rat): 93,458 mg/kg Acute oral toxicity

Method: Acute toxicity estimate

Acute dermal toxicity : LD 50 (Rabbit): 2,599 mg/kg

Method: Acute toxicity estimate

Components:

OLEFIN POLYMER:

Acute oral toxicity : LD 50 (Rat): > 3,000 mg/kg

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

: LD50 (Rat): > 2,000 - 5,000 mg/kg Acute oral toxicity

Remarks: Information given is based on data obtained from

similar substances.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Information given is based on data obtained from

similar substances.

MOLYBDENUM DISULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

: LC 50 (Rat): > 2.82 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: No adverse effect has been observed in acute

inhalation toxicity tests.

Valvoline.	Page: 8
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Not irritating to skin

Remarks: May cause skin irritation in susceptible persons.

Components:

OLEFIN POLYMER:

Result: Not irritating to skin

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result: Irritating to skin

MOLYBDENUM DISULFIDE: Result: Not irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

OLEFIN POLYMER:

Result: Not irritating to eyes

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Result: Corrosive to eyes

MOLYBDENUM DISULFIDE:

Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Biodegradability : Biodegradation: 1.5 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal., Harmful to aquatic life

with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

U.S. DOT - ROAD

0.01 2 0			
	Not dangerous goods		

CFR_RAIL_C

Not dangerous goods	

U.S. DOT - INLAND WATERWAYS

Not dangerous goods	

TDG ROAD C

Not dangerous goods

TDG_RAIL_C

Not dangerous	s goods

TDG_INWT_C

Not dangerous goods	

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

MΧ	DG
171/	-

- 5	
	Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) Component(s)SARA 313

reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

PROPRIETARY OF Synpower Grease -Not Assigned 90.00 -R0257033 100.00 %

OLEFIN POLYMER 9002-88-4 5.00 - 10.00 %

New Jersey Right To Know

PROPRIETARY OF Synpower Grease -90.00 -Not Assigned R0257033 100.00 %

OLEFIN POLYMER 9002-88-4 5.00 - 10.00 %

Phosphorodithioic acid, mixed O,O-bis(iso-68457-79-4 1.00 - 5.00 %

Bu and pentyl) esters, zinc salts

MOLYBDENUM DISULFIDE 1317-33-5 1.00 - 5.00 %

California Prop 65 This product does not contain any chemicals known to State

of California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

DSL : This product contains the following components that are not

on the Canadian DSL nor NDSL.

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

AUSTR : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECL : Not in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H315 Causes skin irritation.
H318 Causes serious eye damage.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA: Federal Insecticide, Fungicide, and Rodenticide Act HMIRC: Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

Valvoline	Page: 14
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0257033
Synpower™ SYNTHETIC GREASE	Version: 1.1
VV985	

RTK : Right to Know WHMIS : Workplace Hazardous Materials Information System