

Material Safety Data Sheet

Hybrid

1. Product and company identification

Product name	: Hybrid
Supplier	: Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607 (800) 333-2156
Manufacturer	: Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607
Code	: 660
MSDS #	: 660
Validation date	: 12/5/2012.
Print date	: 12/5/2012.
In case of emergency	: Chemtrec (800) 424-9300
Product type	: Liquid.

2. Hazards identification

Emergency overview		
Physical state	:	Liquid.
Color	:	White.
Odor	:	Characteristic.
Signal word	:	CAUTION!
Hazard statements	:	MAY CAUSE EYE AND SKIN IRRITATION.
Precautionary measures	:	Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Routes of entry	:	Dermal contact. Eye contact. Ingestion.
Potential acute health effect	<u>ts</u>	
Inhalation	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.
Skin	:	Slightly irritating to the skin.
Eyes	:	Moderately irritating to eyes.
Potential chronic health effe	<u>ects</u>	
Chronic effects	:	No known significant effects or critical hazards.
Carcinogenicity	1	No known significant effects or critical hazards.
Mutagenicity	1	No known significant effects or critical hazards.
Teratogenicity	1	No known significant effects or critical hazards.
Developmental effects	1	No known significant effects or critical hazards.
Fertility effects	1	No known significant effects or critical hazards.
Medical conditions aggravated by over- exposure	:	None known.
See toxicological information	on (S	Section 11)

Hybrid

Г

3. Composition/information on ingredients

Name	CAS number	%
2-(2-ethoxyethoxy)ethanol	111-90-0	1 - 5
tris(2-butoxyethyl) phosphate	78-51-3	1 - 5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures		
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. In case of contact with eyes, rinse immediately with plenty of water.	
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.	
Inhalation	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.	
Ingestion	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.	
Notes to physician	 No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 	

5. Fire-fighting measures

Flammability of the product	: In a fire or if heated, a pressure increase will occur and the container may burst.
Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous thermal decomposition products	 Decomposition products may include the following materials: carbon dioxide carbon monoxide phosphorus oxides
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mi Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).	st.
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods for cleaning up		
12/5/2012.	660	2/8

6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

 Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Ingredient	Exposure limits	
2-(2-ethoxyethoxy)ethanol	AIHA WEEL (United States, 5/2010). TWA: 25 ppm 8 hour(s).	
Recommended monitoring procedures	: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.	
Engineering measures	: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriat techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety shower are close to the workstation location.	
Personal protection		
Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.	
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. <1 hours (breakthrough time): disposable vinyl	
12/5/2012	660 3/	

8. Exposure controls/personal protection

Eyes	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: safety glasses with side-shields
Skin	:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state	: Liquid.
Flash point	: Closed cup: Not applicable. [Product does not sustain combustion.]
Color	: White.
Odor	: Characteristic.
рН	: 8 to 8.8
Relative density	: 1.0265
Dispersibility properties	: Partially dispersible in the following materials: cold water.
Solubility	: Partially soluble in the following materials: cold water.

10. Stability and reactivity

Chemical stability	: The product is stable.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity					
Product/ingredient name	Result	Species	Dos	•	Exposure
tris(2-butoxyethyl) phosphate 2-(2-ethoxyethoxy)ethanol	LD50 Oral LD50 Oral	Rat Rat	3 g/k 7500	g · · · · · · · · · · · · · · · · · · ·	-
Conclusion/Summary	Not available.		·	·	
Chronic toxicity					
Conclusion/Summary	: Not available.				
Irritation/Corrosion					
Product/ingredient name	Result	Species	Score	Exposure	Observation
tris(2-butoxyethyl) phosphate	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
2-(2-ethoxyethoxy)ethanol	Eyes - Mild irritant	Rabbit	-	125 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
0/5/2012		60	I	1	I

11. Toxicological information

			milligrams	
Conclusion/Summary	: Not available.	I.		
<u>Sensitizer</u>				
Conclusion/Summary	: Not available.			
Carcinogenicity				
Conclusion/Summary	: Not available.			
<u>Mutagenicity</u>				
Conclusion/Summary	: Not available.			
Teratogenicity				
Conclusion/Summary	: Not available.			
Reproductive toxicity				
Conclusion/Summary	: Not available.			

12. Ecological information

Product/ingredient name	Result	Species	Exposure
tris(2-butoxyethyl) phosphate	Acute LC50 11200 ug/L Fresh water	Fish - Pimephales promelas - 31 days - 19.6 mm - 0.119 g	96 hours
2-(2-ethoxyethoxy)ethanol	Acute LC50 3340000 ug/L Fresh water	Daphnia - Daphnia magna - Neonate - 0 to 24 hours	48 hours
	Acute LC50 6010000 ug/L Fresh water	Fish - Ictalurus punctatus - 0.72 g	96 hours
Conclusion/Summary	Not available.	•	
Persistence/degradability			
Conclusion/Summary	: Not available.		

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		-
TDG Classification	Not regulated.	-	-	-		-
Mexico Classification	Not regulated.	-	-	-		-
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG* : Packing group

15. Regulatory information

· · · · · · · · · · · · · · · · · · ·			
HCS Classification	: Irritating material		
U.S. Federal regulations	hoxy)propanol es: 5-chloro-2-mether (2-methoxymethyle t determined mined. cyethyl) phosphate	hyl-2H-isothiazol-3- ethoxy)propanol	
	SARA 302/304/311/312 extremely hazardous s SARA 302/304 emergency planning and notifi SARA 302/304/311/312 hazardous chemicals: SARA 311/312 MSDS distribution - chemical i Diethylene glycol ethyl ether: Fire hazard, Immed	ication: No produc 2-(2-ethoxyethoxy inventory - hazard	ts were found.)ethanol I identification :
	Clean Water Act (CWA) 311: potassium hydrox	ide	
Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)	: Listed		
Clean Air Act Section 602 Class I Substances	: Not listed		
Clean Air Act Section 602 Class II Substances	: Not listed		
DEA List I Chemicals (Precursor Chemicals)	: Not listed		
DEA List II Chemicals (Essential Chemicals)	: Not listed		
<u>SARA 313</u>			
	Product name	CAS number	Concentration

	Product name	CAS number	Concentration
Form R - Reporting requirements	2-(2-ethoxyethoxy)ethanol	111-90-0	1 - 5
Supplier notification	2-(2-ethoxyethoxy)ethanol	111-90-0	1 - 5

15. Regulatory information

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations		
Massachusetts	:	None of the components are listed.
New York	1	None of the components are listed.
New Jersey	1	The following components are listed: GLYCOL ETHERS
Pennsylvania	:	The following components are listed: GLYCOL ETHERS
Canada inventory	1	Not determined.
International regulations		
International lists	:	Australia inventory (AICS): Not determined. China inventory (IECSC): Not determined. Japan inventory: Not determined. Korea inventory: Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined.
Chemical Weapons Convention List Schedule I Chemicals	:	Not listed
Chemical Weapons Convention List Schedule Il Chemicals	:	Not listed
Chemical Weapons Convention List Schedule III Chemicals	:	Not listed

16. Other information

Label requirements Hazardous Material Information System (U.S.A.) MAY CAUSE EYE AND SKIN IRRITATION.



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

2

t

•

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing	:	12/5/2012.
Date of issue	:	12/5/2012.
Date of previous issue	1	8/31/2012.
Version	:	0.03
Prepared by	:	Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.